

Shenzhen DOKE Electronic Co.,Ltd.

EU DECLARATION OF CONFORMITY

in accordance with
Annex VI of Directive 2014/53/EU of the European Parliament and of the Council

1. For the following Radio equipment: Mobile Phone

Product name / Number (s): Mobile Phone / A52 PRO(4+128GB)

Tradename or Brand: Blackview

Software: A52Pro_EEA_S6067B_V1.0

Hardware number: S682_V1

2. Name and address of the manufacturer: 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

Manufacturer: Shenzhen DOKE Electronic Co.,Ltd.

3. This declaration of conformity is issued under the sole responsibility of the Manufacturer.

4. Object of the declaration (identification of the radio equipment allowing traceability; it may include a colour image of sufficient clarity where necessary for the identification of the radio equipment):

PIFA Antenna: BT/Wi-Fi 2.4G: 1.37 dBi; Wi-Fi 5G: 1.29 dBi;

GSM900: -1.05dBi; DCS1800:0.63dBi; WCDMA Band I : -0.91dBi ;Band VIII: -1.05dBi;

LTE Band1:0.91dBi; Band3:0.63dBi; Band7:1.12dBi; Band8:-1.05dBi; Band20:-0.71dBi; Band40:1.14dBi;

Adapter:

Model: QZ-01000EA00

Input: 100-240V~50/60Hz 0.3A

Output: 5.0V ---2.0A (10.0W)

Manufacturer: Guangdong Quanzhi Technology Co., Ltd.

Rechargeable Li-ion Battery; Model: LiHPV466595PFH; Specification: DC 3.85V, 5180mAh, 19.943Wh;

Manufacturer: GUANGDONG FENGHUA NEW ENERGY CO., LTD.

USB Cable: 100cm;



5. The object of the declaration described above is in conformity with the relevant Union harmonization legislation: Directive 2014/53/EU (RED)

6. References to the relevant harmonized standards used or references to the other technical specifications in relation to which conformity is declared:

Referenced Standards:	
Article 3.2 Radio:	ETSI EN 301 511 V12.5.1 (2017-03); ETSI EN 301 908-1 V13.1.1 (2019-11); ETSI EN 301 908-2 V13.1.1 (2020-06); ETSI EN 301 908-13 V13.1.1 (2019-11); ETSI EN 300 328 V2.2.2 (2019-07); ETSI EN 301 893 V2.1.1 (2017-05); ETSI EN 303 413 V1.2.1 (2021-04); ETSI EN 303 345-1 V1.1.1 (2019-06); ETSI EN 303 345-3 V1.1.1 (2021-06);
Article 3.1 EMC:	ETSI EN 301 489-1 V2.2.3 (2019-11) ETSI EN 301 489-17 V3.2.4 (2020-09) ETSI EN 301 489-19 V2.1.1 (2019-04) ETSI EN 301 489-52 V1.2.1 (2021-11) EN 55032:2015+A1:2020 EN 55035:2017+A11:2020 EN IEC 61000-3-2:2019+A1:2021 EN 61000-3-3:2013+A2:2021
Article 3.1a Safety:	EN IEC 62368-1:2020+A11:2020
Article 3.1a Health	EN 50360:2017; EN 50566:2017; EN 62209-1:2016; EN 62209-2:2010; EN 62479:2010;

7. Notified Body Name: Eurofins Electrical and Electronic Testing NA, Inc.

Notified Body Number: 0980

Notified Body Assessment Performed: Module B/C on Article 3.1a, 3.1b, 3.2

EU-type examination certificate number: 2551-09-2023-230299

8. Where applicable, description of accessories and components, including software, which allow the radio equipment to operate as intended and covered by the EU declaration of conformity: User instructions are provided in the User Manual. The Software and Hardware versions are specified above.

9. Additional information:

Referring to Article 10.2 of the Directive, this equipment is so constructed that it can be operated in all Member States, without infringing applicable requirements on the use of radio spectrum.

Referring to Article 10.10 of the Directive, there are no restrictions on putting this equipment into service or of requirements for authorisation of use. Please refer to the User Manual for details.

RF Specification:

Function	Operation Frequency	Max RF output power:
BLE	2402MHz~2480MHz	-2.43 dBm
BT(BR+EDR)	2402MHz~2480MHz	6.62 dBm
WIFI 802.11b/g/n(HT20/40)	802.11b/g/n(20MHz): 2412~2472MHz; 802.11n(40MHz):2422~2462MHz	16.6 dBm
Wi-Fi 5.2G(802.11a/n20/n40/a c20/ac40/ac80)	802.11a/ n20/ac20:5180MHz~5240MHz 802.11 n40/ac40:5190MHz~5230MHz 802.11 ac80:5210MHz	10.17 dBm
GSM/GPRS/EGPRS 900	TX(Uplink):880M-915MHZ; RX(Downlink):925M-960MHZ	33.59dBm
GSM/GPRS/EGPRS 1800	TX(Uplink):1710M-1785MHZ; RX(Downlink):1805M-1880MHZ	31.95 dBm
WCDMA B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	23.68 dBm
WCDMA B8	TX(Uplink): 880-915MHz; RX(Downlink):925-960MHz	23.54 dBm
LTE FDD B1	TX(Uplink):1920-1980MHz; RX(Downlink):2110-2170MHz	24.06 dBm
LTE FDD B3	TX(Uplink) :1710-1785MHz; RX(Downlink):1805-1880MHz	23.93 dBm
LTE FDD B7	TX(Uplink) :2500-2570MHz; RX(Downlink):2620-2690MHz	24.2dBm
LTE FDD B8	TX(Uplink): 880MHz to 915 MHz RX(Downlink): 925 MHz to 960 MHz	23.73dBm
LTE FDD B20	TX(Uplink) 832MHz~862MHz; RX(Downlink)791MHz~821MHz	23.33dBm
LTE TDD B40	TX(Uplink)& RX(Downlink) 2300 MHz to 2400 MHz	24.51dBm
FM	Rx(Downlink): 87.5MHz~108MHz	--
GPS	Rx(Downlink): 1.57542GHz	--

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used close to the body (at a minimum distance of 5mm/0mm) are:

Max SAR Value(W/kg) Limit is 2.0(W/kg) for 10-g	10-g Head	1.358
	10-g Body	1.493
Limit is 4.0(W/kg) for 10-g	10-g Member DAS	3.798

On behalf of:

Manufacturer: [Shenzhen DOKE Electronic Co.,Ltd.](#)

Add: [801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China..](#)

(place and date of issue): [2023/09/18](#)

(name, function):

(signature):