

Declaration of Conformity (DoC)

We, **Shenzhen DOKE Electronic Co.,Ltd.**

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

Declare that the DoC is issued under our sole responsibility and belongs to the following product(s):

Product Type:	Table PC
Trademark:	Blackview
Model Number(s):	ZENO 10

(Name of product, type or model, batch or serial number)

System components:

For Bluetooth/2.4G WIFI/5G WIFI/FM/GPS/GLONASS/GALILEO/BDS/GSM/WCDMA/

LTE/5G NR: PIFA Antenna

Bluetooth/2.4G

WIFI:3.19dBi

5.2G WIFI: 3.81dBi

5.8G WIFI:3.81dBi

GSM 900: -1.12dBi

GSM 1800: 0.83dBi

WCDMA Band I: 0.95dBi

WCDMA Band VIII:-1.12dBi

LTE band 1:0.95dBi

LTE band 3: 0.83dBi

LTE band 7: 1.32dBi

LTE band 8: -1.12dBi

LTE band 20: -0.81dBi

LTE band 28: -1.36dBi

NR n1: 0.95dBi

NR n3: 0.83dBi

NR n8: -1.12dBi

NR n20: -0.83dBi

NR n28: -1.36dBi

NR n40: 1.35dBi

NR n77: 2.5dBi

NR n78: 2.7dBi

Adapter Information:

Model: HJ-FC001KF-EU

Input: 100-240V 50/60Hz 0.6A

Output: 5.0V = 3.0A 15.0W

9.0V = 2.0A 18.0W

12.0V = 1.5A 18.0W

Manufacturer: Shenzhen Huajin Electronics Co.,Ltd.

Rechargeable Li-ion Battery:

Model: Li318991PHVUTL-A;

Rated Voltage:3.87 V

Charge Limit Voltage: 4.45 V

Capacity:8800 mAh;

Manufacturer: SHENZHEN UTILITY ENERGY CO.,LTD.



The object of the declaration described above is in conformity with the essential requirements of the relevant Union harmonization legislation: Radio Equipment Directive *RED (2014/53/EU)*.

The following *harmonized* standards and technical specifications have been applied:

HEALTH & SAFETY (Art. 3(1)(a)):

EN IEC 62368-1:2020+A11:2020

EN 50566: 2017/A1:2023

EN IEC/EEE 62209-1528:2021

EN 50663:2017:EN 62479:2010

EMC (Art. 3(1)(b)):

EN 301 489-1 V2.2.3 (2019-11)

ETSI EN 301 489-3 V2.3.2 (2023-01)

EN 301 489-17 V3.3.1 (2024-09)

EN 301 489-19 V2.2.1 (2022-09)

EN 301 489-52 V1.3.1 (2024-11)

EN 55032:2015/A11:2020

EN IEC 61000-3-2:2019/A2:2024

EN 61000-3-3:2013/A2:2021/AC:2022

EN 55035:2017/A11:2020

Radio Spectrum (Article 3.2):

EN 300 328 V2.2.2 (2019-07)

ETSI EN 301 893 V2.1.1 (2017-05)

ETSI EN 300 440 V2.2.1 (2018-07)

ETSI EN 303 345-1 V1.1.1 (2019-06)

ETSI EN 303 345-3 V1.1.1 (2021-06)

ETSI EN 303 413 V1.2.1 (2021-04)

ETSI EN 301 511 V12.5.1 (2017-03)

ETSI TS 151 010-1 V13.14.0(2024-06)

ETSI EN 301 908-1 V15.2.1 (2023-01)

ETSI EN 301 908-2 V13.1.1 (2020-06)
ETSI EN 301 908-13 V13.3.1 (2024-10)
ETSI TS 138 521-1 V17.6.1(2022-10)
ETSI TS 138 521-3 V17.7.0(2023-01)
ETSI EN 301 908-1 V15.2.1(2023-01)
ETSI EN 301 908-25 V15.1.1(2024-10)

Notified Body Involved:

Notified Body Name: DERYCOM CERTIFICATION SERVICES, INC.

Notified Body Number: 3052

Notified Body Assessment Performed: Module B/C on Article 3.1a, 3.1b, 3.2

EU-type examination certificate number: JEC-29

RF Specification:

Function	Operation Frequency	Max RF output power:
BLE	2402MHz~2480MHz	3.63dBm
BT(BR+EDR)	2402MHz~2480MHz	3.69dBm
WIFI 802.11b/g/n(20MHz) 802.11n(40MHz):	802.11b/g/n(20MHz): 2412~2472MHz; 802.11n(40MHz):2422~2462MHz	13.08dBm
Wi-Fi 5.2G(802.11a/n/ac (20MHz) 802.11n/ac (40MHz) 802.11ac(80MHz)	5180MHz~5240MHz	12.63dBm
Wi-Fi 5.8G(802.11a/n/ac (20MHz) 802.11n/ac (40MHz) 802.11ac(80MHz)	5745MHz~5825MHz	11.88dBm
GSM/GPRS/EGPRS 900	TX:880M- 915MHZ;RX:925M- 960MHZ	31.69dBm
GSM/GPRS/EGPRS 1800	TX:1710M-1785MHZ;RX:1805M-1880MHZ	28.95dBm
WCDMA B1	TX:1920-1980MHZ;RX:2110-2170MHZ	24.62dBm
WCDMA B8	TX: 880-915MHZ;RX:925-960MHZ	24.33dBm
LTE FDD B1	(UL)1920MHz~1980MHz,(DL)2110MHz~2170MHz	22.56dBm
LTE FDD B3	(UL)1710MHz~1785MHz,(DL)1805MHz~1880MHz	23.95dBm
LTE FDD B7	(UL)2500MHz~2570MHz,(DL)2620MHz~2690MHz	23.67dBm
LTE FDD B8	(UL)880MHz~915MHz,(DL)925MHz~960MHz	23.32dBm
LTE FDD B20	(UL)832MHz~862MHz,(DL)791MHz~821MHz	23.97dBm
LTE FDD B28	(UL)703MHz~748MHz,(DL)758MHz~803MHz	23.39dBm
NR n1	(UL)1920MHz~1980MHz, (DL)2110MHz~2170MHz	21.58dBm
NR n3	(UL)1710MHz~1785MHz, (DL)1805MHz~1880MHz	22.87dBm
NR n8	(UL)880MHz~915MHz, (DL)925MHz~960MHz	23.03dBm
NR n20	(UL)832MHz~862MHz, (DL)791MHz~821MHz	23.65dBm
NR n28	(UL)703MHz~748MHz, (DL)758MHz~803MHz	22.94dBm
NR n40	(UL)2300MHz~2400MHz, (DL)2300MHz~2400MHz	22.13dBm
NR n77	(UL)3300MHz~4200MHz, (DL)3300MHz~4200MHz	25.21dBm
NR n78	(UL)3300MHz~3800MHz, (DL)3300MHz~3800MHz	25.52dBm
FM	Rx: 87.5MHz~108MHz	--
GPS	1575.42 MHz	--
BDS	1561.098 MHz	
Galileo	1575.42 MHz	
GLONASS	1602 MHz	

Tests for SAR are conducted using standard operating positions with the device transmitting at its highest certified power level in all tested frequency bands. The maximum SAR values tested on this device when used in its normal position at the ear and when used close to the body (at a minimum distance of 5mm/0mm) are:

Max SAR Value(W/kg) Limit is 2.0(W/kg) for 10-g	10-g Body	1.320 W/kg
Limit is 4.0(W/kg) for 10-g	10-g Member DAS	1.320 W/kg

Technical file held by: Shenzhen DOKE Electronic Co., Ltd

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.

Signed for and on behalf of:


Shenzhen DOKE Electronic Co., Ltd

Name and Title:

qinzhaoyang/Manager

Address:

801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.



Signature of Authorized Person

2025-09-25